

Flex Strip

A Series LED Flex Strip

Product Description

VaOpto's LED Flex Strip Series is energy efficient, lead free, cold lighting source, UV free, and long lasting, meaning less lamp maintenance. Compared to standard light strips, VaOpto's LED Flex Strip Series reduce energy consumption by 50%.

Product Information

- Available in various colors and RGB
- Cool White: CRI > 75
- Neutral White: CRI > 80
- Warm White: CRI > 85
- Beam Angle = 120°
- cULus #E321933
- Three-years limited warranty



Ordering Information


A0 Series with 3528 LEDs, Non-waterproof, (RGB is 5050 LEDs)

Part Number	Length (ft)	No. of LEDs	Power (W)	Input Voltage (VDC)	Current (A)	CCT/Wavelength	Lumens (lm)	Lumens /ft	Minimum Working Unit	Price
VO-FS-R-12A0	16.4	300	24	12	2	624nm (Red)	435	26.5	⊗ 3 LED / 5CM ⊗	
VO-FS-Y-12A0	16.4	300	24	12	2	590nm (Yellow)	435	26.5	⊗ 3 LED / 5CM ⊗	
VO-FS-G-12A0	16.4	300	24	12	2	515nm (Green)	900	54.9	⊗ 3 LED / 5CM ⊗	
VO-FS-B-12A0	16.4	300	24	12	2	470nm (Blue)	285	17.4	⊗ 3 LED / 5CM ⊗	
VO-FS-CW-12A0	16.4	300	24	12	2	6500K	1800	109.8	⊗ 3 LED / 5CM ⊗	
VO-FS-NW-12A0	16.4	300	24	12	2	4100K	1670	101.8	⊗ 3 LED / 5CM ⊗	
VO-FS-WW-12A0	16.4	300	24	12	2	3500K	1600	97.6	⊗ 3 LED / 5CM ⊗	
VO-FS-XW-12A0	16.4	300	24	12	2	2700K	1600	97.6	⊗ 3 LED / 5CM ⊗	
VO-FS-RGB-12A0	16.4	180	36	12	3	625, 515, 470 nm	-	-	⊗ 3 LED / 8.3CM ⊗	
VO-FS-R-24A0	16.4	300	24	24	1	624nm (Red)	435	26.5	⊗ 6 LED / 10CM ⊗	
VO-FS-Y-24A0	16.4	300	24	24	1	590nm (Yellow)	435	26.5	⊗ 6 LED / 10CM ⊗	
VO-FS-G-24A0	16.4	300	24	24	1	515nm (Green)	900	54.9	⊗ 6 LED / 10CM ⊗	
VO-FS-B-24A0	16.4	300	24	24	1	470nm (Blue)	285	17.4	⊗ 6 LED / 10CM ⊗	
VO-FS-CW-24A0	16.4	300	24	24	1	6500K	1800	109.8	⊗ 6 LED / 10CM ⊗	
VO-FS-NW-24A0	16.4	300	24	24	1	4100K	1670	101.8	⊗ 6 LED / 10CM ⊗	
VO-FS-WW-24A0	16.4	300	24	24	1	3500K	1600	97.6	⊗ 6 LED / 10CM ⊗	
VO-FS-XW-24A0	16.4	300	24	24	1	2700K	1600	97.6	⊗ 6 LED / 10CM ⊗	
VO-FS-RGB-24A0	16.4	180	36	24	1.5	625, 515, 470 nm	-	-	⊗ 6 LED / 16.6CM ⊗	

Outline Dimension

A0 Series

Length	Width	Height
196.8 in	0.31 in	0.094 in



unit: mm



Flex Strip

A Series LED Flex Strip




A1-65 Series with 3528 LEDs, Waterproof (RGB is 5050 LEDs)

Part Number	Length (ft/ Roll)	No. of LEDs (Pcs/Roll)	CCT/ Wavelength	Input Voltage (VDC)	Power (W/Roll)	Current (A/Roll)	Lumens (lm/ Roll)	Watts (W/ft)	Current (A/ft)	Lumens (lm/ft)	Price
VO-FS-R-12A1-65	16.4	300	624nm (Red)	12	24	2	430	1.46	0.12	26.2	
VO-FS-Y-12A1-65	16.4	300	590nm (Yellow)	12	24	2	430	1.46	0.12	26.2	
VO-FS-G-12A1-65	16.4	300	515nm (Green)	12	24	2	890	1.46	0.12	54.3	
VO-FS-B-12A1-65	16.4	300	470nm (Blue)	12	24	2	280	1.46	0.12	17.1	
VO-FS-CW-12A1-65	16.4	300	7000K	12	24	2	1770	1.46	0.12	107.9	
VO-FS-NW-12A1-65	16.4	300	4600K	12	24	2	1640	1.46	0.12	100.0	
VO-FS-WW-12A1-65	16.4	300	3900K	12	24	2	1560	1.46	0.12	95.1	
VO-FS-XW-12A1-65	16.4	300	3100K	12	24	2	1510	1.46	0.12	92.1	
VO-FS-RGB-12A1-65	16.4	180	625, 515, 470nm	12	36	3	-	2.20	0.18	-	
VO-FS-R-24A1-65	16.4	300	624nm (Red)	24	24	1	430	1.46	0.06	26.2	
VO-FS-Y-24A1-65	16.4	300	590nm (Yellow)	24	24	1	430	1.46	0.06	26.2	
VO-FS-G-24A1-65	16.4	300	515nm (Green)	24	24	1	890	1.46	0.06	54.3	
VO-FS-B-24A1-65	16.4	300	470nm (Blue)	24	24	1	280	1.46	0.06	17.1	
VO-FS-CW-24A1-65	16.4	300	7000K	24	24	1	1770	1.46	0.06	107.9	
VO-FS-NW-24A1-65	16.4	300	4600K	24	24	1	1640	1.46	0.06	100.0	
VO-FS-WW-24A1-65	16.4	300	3900K	24	24	1	1560	1.46	0.06	95.1	
VO-FS-XW-24A1-65	16.4	300	3100K	24	24	1	1510	1.46	0.06	92.1	
VO-FS-RGB-24A1-65	16.4	180	625, 515, 470nm	24	36	1.5	-	2.20	0.09	-	

Outline Dimension

A1-65 Series

Length	Width	Height
196.8 in	0.31 in	0.118 in



unit: mm

Minimum and Maximum Ratings

Parameters	Values
Operating Temperature	-22°F – 185°F
Storage Temperature	-22°F – 185°F